

LED Escape sign luminaire Luminaire with local battery supply for 3h emergency lighting for maintained or non-maintained mode, automatic or central testing of emergency lighting function; wall mounted; die-cast aluminium base unit in white powder-coated finish. LED control gear with "maintenance function" ensures constant luminous flux over the entire lifetime of the luminaire. Plug-in terminals for through-wiring up to 2.5 mm². Cable feed from any side, flexible cable guide in housing base. No tools required to fit frameless pictogram or to replace the NiMH battery in the self-contained models (NT1 and NT3); power supply: 220/240V AC. Rotary switch for mechanical address-setting; degree of protection: IP54, class of protection: SC1; non-maintained and maintained mode possible, Maintained mode: +5°C to +30°C, Non-maintained mode: +5°C to +35°C; Dimensions: 201 x 87 x 55 mm; weight: 0.58 kg; Luminaire wired with halogen-free leads Please order escape signs separately.


Příslušenství: ERGOSIGN C RZ-1U

22166887

Escape sign for ERGOSIGN AW/EW LED. Diffuser made of opal PC with integral optical waveguide panel and reflector; digitally printed pictogram; crystal-clear TPE provides continuous seal around sign; luminance > 200 cd/m²; downward light outlet provides extra illumination of escape route. Arrow pointing down; sign fitted without tools. Recognition distance: EN-16 m. Dimensions: 201 x 87 x 16 mm, weight: 0.18 kg




ZS_ONL_F_ERGOSIGN_AB_komplett_RZ_U.jpg



ZS_ONL_M_ergo_Anbau.wmf

Křivka svítivosti

STD – standard



D35489AA_ERGOSIGN_C_AW_LED_NT3.Idt

- Světelný zdroj: LED
- Světelný tok*: 17 lm
- Světelný výkon svítidel*: 6 lm/W
- Předřadník: 1 x 89800074 EM power1 B LED NTx LO TA
- Barevná tolerance v místě (MacAdam)*: 4
- Střední dimenzovaná životnost*: 50000h L70 při/u 25°C
- Příkon svítidla*: 2.88 W Lambda = 0.4
- Vyměření doby provozu: 3 h

Hodnoty označené * představují stanovené rozměrové hodnoty. Výkon a světelný tok podléhají zpočátku toleranci až do +/- 10 %. Tolerance barevné teploty: % K Pokud není uvedeno jinak, platí hodnoty pro okolní teplotu 25°C.